## CUNFIDENTIAL

P-101C

13 April 1956

BUBJ	ECT : Meeting	
	1. Time and Place of Meeting: The meeting was held 9 April 1956	
at		
	2. Attendance:	
	3. Discussion:	
	a. After introductions were preformed signed	
	the required secrecy agreement. Our particular security require-	
	ments were explained as to non-association and personnel clearance. stated that a complete tour of the plant	
	would be impossible as he had no record of our clearances and	
	pert of his plant was currently engaged in a classified govern-	
	ment contract.	
ī	b. Before touring the unclassified portion of his plant,	
	explained some of their past efforts. He demonstrated	
	explained some of their past efforts. He demonstrated their "Screaming Meamie" which is a heat detector using a PbS	
	explained some of their past efforts. He demonstrated	
	explained some of their past efforts. He demonstrated their "Screaming Meanie" which is a heat detector using a PbS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive explifier into heat oscillator. The final output drives a speaker. The sural signal is that of	
	explained some of their past efforts. He demonstrated their "Screaming Meanie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon	
	explained some of their past efforts. He demonstrated their "Screaming Meamie" which is a heat detector using a PbS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the	
	explained some of their past efforts. He demonstrated their "Screaming Meanie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is	
	explained some of their past efforts. He demonstrated their "Screaming Measie" which is a heat detector using a PbS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal	
	explained some of their past efforts. He demonstrated their "Screaming Meanie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  c. mentioned that his plant manufactured	2
	explained some of their past efforts. He demonstrated their "Screening Meanie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  c. mentioned that his plant manufactured thermistors with time constants in the order of 200 micro secs.	2
	explained some of their past efforts. He demonstrated their "Screaming Meanie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  c. mentioned that his plant manufactured	2
	their "Screening Measie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  c	2
	explained some of their past efforts. He demonstrated their "Screaming Meamie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  c	2
	explained some of their past efforts. He demonstrated their "Screaming Meamie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The mural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  c. mentioned that his plant manufactured thermistors with time constants in the order of 200 micro secs. which is somewhat faster than Bell Labs have done.  d. They also manufacture: Black Bodies with ranges to 230° C or 650° C. Radiometers in 4" and 8" sizes were a natural outgrowth of the Black Bodies. The Bureau of Standards	2
	explained some of their past efforts. He demonstrated their "Screaming Meamie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  c	2
MENT NO.	explained some of their past efforts. He demonstrated their "Screaming Meamie" which is a heat detector using a PhS (Ektron) detector. The signal from the Ektron detector feeds through a voltage sensitive amplifier into heat oscillator. The final output drives a speaker. The sural signal is that of an oscillator which changes frequency when radiation falls upon the Ektron detector. The present, no signal, frequency of the oscillator appears to be approximately 15-16,000 cps. Signal causes a lowering of frequency at present although it is believed that this could be reversed if desirable.  C	2

PATE: 690/80 REVIEWER: 010956

Declassified in Part - Sanitized Copy Approved for Release 2012/07/16: CIA-RDP78-03300A001600010021-9

Andreas and a second of the contract of the co

## CONFIDENTIAL

is engaged in automation. They have manufactured devices to operate turnet lathes. They are currently making for Mallory machines to assemble their mercury batteries at a rate of 50/minutes per machine. An effort (for the petroleum industry) is being made to develop automatic refractomaters.

- f. A device was mentioned that takes heat pictures. Details were not desclosed as to the method but the claims were as follows:
  - (1) quantitative picture obviously produced by scan lines taken on a Polaroid Land Camera
  - (2) Sensitive to at least 30 C differentials in temperature. Exposure time 15 minutes. A classified effort is being made to reduce the exposure time with the comment from that the time has been reduced to less than one minute.
- g. The plant consists of some 22,000 mg. ft. and employs approximately 110 persons. Their Chief IR men is stated that 6% of their efforts were in Infrared.
- h. A 9 man machine shop appears to be efficiently run and well equipped. Production facilities for limited quantities appear to be adequate for electronic and mechanical parts. Optical components are purchased outside.
- was given our sterile address and some PSQ's and was requested to send the PSQ's on people who would need to be vitting.

## 4. Recommendations:

It is recommended that APD consider this company as a possible source of a pessive IR device and contingent upon the results, to consider further developmental and production contracts.

TEE/APD

## Distribution:

1-2-387114

- 1 P-101B
- 1 P-101C
- 1 P-1010
- 1 Panel
- 1 BW
- 1 RTW

CONFIDENTIAL

Declassified in Part - Sanitized Copy Approved for Release 2012/07/16: CIA-RDP78-03300A001600010021-9

----

25X1

25X1

25X1 25X1

25X1

25X1